

PRODUCT DATA

Piezoelectric Accelerometer Charge Accelerometer — Type 4371, 4371 S and 4371 V

FEATURES

- General purpose
- High sensitivity
- High frequency
- Vibration testing

Description

Type 4371 is a piezoelectric, DeltaShear[®], Unigain[®] accelerometer with side connector. Type 4371 features 10–32 UNF receptacle for output connection and can be mounted on the object by means of a 10–32 UNF threaded steel stud.

Characteristics



This piezoelectric accelerometer may be treated as a charge source. Its sensitivity is expressed in terms of charge per unit acceleration (pC/g).

The DeltaShear design involves three piezoelectric elements and three masses arranged in a triangular configuration around a triangular centre post. The ring prestresses the piezoelectric elements to give a high degree of linearity. The charge is collected between the housing and the clamping ring. The piezoelectric element used is a PZ 23 lead zirconate titanate element. The housing material is titanium.



Calibration

The sensitivity given in the calibration chart has been measured at 159.2 Hz and an acceleration of 10 g. For 99.9% confidence level, the accuracy of the factory calibration is $\pm 2\%$.



Specifications – Charge Accelerometer Type 4371, 4371 S and 4371 V

	Units	4371/4371 S	4371 V
Dynamic Characteristics			
Charge Sensitivity (@ 159.2 Hz)	pC/g	9.8 ± 2%	9.8 ± 15%
Frequency Response		See typical Amplitude Response	
Mounted Resonance Frequency	kHz	42	
Amplitude Response ±10% [1]	Hz	0.1 to 12600	
Transverse Sensitivity	%	<4	
Transverse Resonance Frequency	kHz	15	
Electrical Characteristics			
Min. Leakage Resistance @ 20°C	GΩ	≥20	
Capacitance	pF	1200	
Grounding		Signal ground connected to case	
Environmental Characteristics			
Temperature Range	°C (°F)	-55 to 250 (-67 to 482)	
Humidity		Welded, sealed	
Max. Operational Sinusoidal Vibration (peak)	g pk	6000	
Max. Operational Shock (± peak)	g pk	20000	
Base Strain Sensitivity	Equiv. g/μ strain	0.002	
Thermal Transient Sensitivity	Equiv. g/°C (g/°F)	0.004 (0.022)	
Magnetic Sensitivity (50 Hz–0.03 Tesla)	g/T	0.4	
Physical Characteristics			
Dimensions		See outline drawing	
Weight	gram (oz.)	11 (0.39)	
Case Material		Titanium	
Connector		10–32 UNF	
Mounting		10–32 UNF × 3.2 mm threaded hole	

[1] Low-end response of the transducer is a function of its associated electronics

Ordering Information

Type 4371 includes the following accessories:

- Carrying box
- Calibration chart
- AO 0038: Low noise cable fitted with 10–32 connectors, 1.2 m
- 10–32 UNF threaded steel stud. Length 12.7 mm

Type 4371 S includes the following accessories:

- Carrying box
- Calibration chart
- AO 0038: Low noise cable fitted with 10–32 connectors, 1.2 m
- 10–32 UNF threaded steel stud. Length 12.7 mm
- UA 0078: Accessory box including:
 - Cementing stud, 10–32 UNF
 - EP610 input adaptor, TNC to 10–32 UNF microdot
 - Mounting magnet, 10–32 UNF thread

- Case of beeswax
- Insulating disk
- Insulating stud
- Steel stud 10–32 UNF × ½"
- Tools

Type 4371 V includes the following accessories:

- Carrying box
- Calibration chart
- 10–32 UNF threaded steel stud. Length 12.7 mm

OPTIONAL ACCESSORIES

- AO 0038: 260°C Teflon® low-noise cable, 10–32 UNF, length 1.2 m (4 ft)
- AO 0122: 250°C, reinforced super low noise cable, 10–32, 3 m (10 ft)
- AO 0231: 260°C Teflon low-noise cable, 10–32 UNF/TNC, length 3 m (10 ft)
- AO 1382: Teflon low noise cable, double screened 10–32, 1.2 m (4 ft)

- DB 0544: 10–32 UNF Round tip
- JJ 0207: 2-pin TNC/10–32 UNF plug adaptor
- JP 0162: 10–32 UNF to TNC connector adaptor
- QA 0013: Hexagonal key for 10–32 UNF studs
- QA 0029: Tap for 10–32 UNF thread
- UA 0559: Mechanical filter for Accelerometer
- UA 0642: Mounting magnet and 2 insulating discs
- UA 0866: Cement stud 10–32 UNF 0.14 mm (set of 25)
- YG 0150: Steel stud 10–32/10–32 with flange
- YJ 0216: Beeswax for mounting
- YP 0080: Probe with sharp tip
- YP 0150: 10–32 UNF insulated stud. Length 12.7 mm
- YQ 2960: 0–32 UNF threaded steel stud. Length 12.7 mm
- YQ 2962: 0–32 UNF threaded steel stud. Length 7.62 mm

Brüel & Kjær reserves the right to change specifications and accessories without notice

HEADQUARTERS: DK-2850 Nærum · Denmark · Telephone: +45 4580 0500 · Fax: +45 4580 1405
www.bksv.com · info@bksv.com

Australia (+61) 2 9889-8888 · Austria (+43) 1 865 74 00 · Brazil (+55) 11 5188-8166 · Canada (+1) 514 695-8225
China (+86) 10 680 29906 · Czech Republic (+420) 2 6702 1100 · Finland (+358) 9-521 300 · France (+33) 1 69 90 71 00
Germany (+49) 421 17 87 0 · Hong Kong (+852) 2548 7486 · Hungary (+36) 1 215 83 05 · Ireland (+353) 1 807 4083
Italy (+39) 0257 68061 · Japan (+81) 3 5715 1612 · Korea (+82) 2 3473 0605 · Netherlands (+31) 318 55 9290
Norway (+47) 66 77 11 55 · Poland (+48) 22 816 75 56 · Portugal (+351) 21 47 11 453 · Singapore (+65) 377 4512
Slovak Republic (+421) 25 443 0701 · Spain (+34) 91 659 0820 · Sweden (+46) 8 449 8600
Switzerland (+41) 44 880 7035 · Taiwan (+886) 2 2502 7255 · United Kingdom (+44) 14 38 739 000
USA (+1) 800 332 2040 · Local representatives and service organisations worldwide