

# SLB-700A/06-1

# SLB-700A/12-1


## Strain Transducer

### Special features

- For monitoring strain on statically and dynamically loaded components, e.g. on cranes, presses and roll stands
- Simple, bolted mounting
- Stainless steel
- Protected against environmental influences



### Dimensions (in mm; 1 mm = 0.03937 inches)



four-wire cable  
length 6 m (SLB-700A/06) or  
12 m (SLB-700A/12)  
Ø approx. 3

### SLB-700A cable wire assignment

Assignment	Color code
Excitation voltage (+)	blue
Excitation voltage (-)	black
Measurement signal (+)	white
Measurement signal (-)	red
Shield	connected to housing

# Specifications

Type		SLB-700A/06	SLB-700A/12
Nominal (rated) measuring range	μm/m	0 ... 500	
Nominal (rated) sensitivity	mV/V	1.5 ±0.15	
Relative zero signal error	%	5	
Relative reversibility error	%	0.5	
Relative linearity error	%	0.5	
Effect of temperature on sensitivity, per 10 K	%	0.2	
Effect of temperature on zero signal, per 10 K	%	0.2	
Output resistance	Ω	1000 ±10	
Input resistance	Ω	> 1000	
Insulation resistance	Ω	> 5 · 10 <sup>10</sup>	
Nominal (rated) range of the excitation voltage	V	2 ... 15	
Nominal (rated) temperature range	°C	-10 ... 40	
Operating temperature range	°C	-20 ... 60	
Storage temperature range	°C	-40 ... 85	
Adapted to a material with a thermal expansion coefficient of	1/°C	12 · 10 <sup>-6</sup>	
Maximum operating strain	μm/m	750	
Restoring force	N	approx. 3110	
Breaking strain	μm/m	1500	
Max. permissible vibrational stress per VDI/VDE 2638	%	150	
Vibration per DIN EN 60068-2-6	Hz	10 ... 500	
Maximum impact load per DIN EN 60068-2-27	g	50	
Degree of protection per DIN EN 60529		IP65	
Mounting bolt tightening torque at least	N·m	8	
nominal (rated) value	N·m	16	
Cable sheath		PUR	
Cable length	m	6	12
Cable diameter	mm	3	

Ordering number	SLB-700A/06-1	SLB-700A/12-1
-----------------	---------------	---------------

Modifications reserved.  
All product descriptions are for general information only. They are not to be understood as a guarantee of quality or durability and do not constitute any liability whatsoever.

## Hottinger Baldwin Messtechnik GmbH

Im Tiefen See 45 · 64293 Darmstadt · Germany  
Tel. +49 6151 803-0 · Fax: +49 6151 803-9100  
E-mail: [info@hbm.com](mailto:info@hbm.com) · [www.hbm.com](http://www.hbm.com)

measure and predict with confidence

